LIST OF TABLES

TABLE		PAGE
3-1	MTI Canceller Transfer Properties	3-59
4-1	Time Intervals That Interfering Radar Pulses Overlap The Rank Quantizer Range Bin Sample Times For Various Combinations Of Interfering And Victim Radars	4-17
4-2	ARTS-IIIA/RDAS Probability Of False Target Hit When Connected To ASR-7 Radar That Is Receiving Interference From One Radar.	4-27
4-3	ARTS-IIIA/RDAS Probability Of False Target Hit When Connected To ASR-7 Radar That Is Receiving Interference From One Radar.	4-28
4-4	ARTS-IIIA/RDAS Probability Of False Target Hit When Connected To ASR-8 Radar That Is Receiving Interference From One Radar.	4-29
4-5	ARTS-IIIA/RDAS Probability Of False Target Hit When Connected To ASR-8 Radar That Is Receiving Interference From Three Radars Of The Same Type.	4-30
4-6	ARTS-IIIA/RDAS Probability Of False Alarm For Typical Detection Parameters And Various Combinations Of Interfering And Victim Radars	4-33
4-7	Average Number Of Azimuth Change Pulse Since Initial Hit For A False Alarm To Occur	4-35
4-8	ARTS-IIIA/RDAS Probability Of Target Hit When Connected To ASR-7 Radar That Is Receiving Interference From One Radar	4-52
4-9	ARTS-IIIA/RDAS Probability Of Target Hit When Connected To ASR-7 Radar That Is Receiving Interference From Three Radars Of The Same Type	4-53
4-10	ARTS-IIIA/RDAS Probability Of Target Hit When Connected To ASR-8 Radar That Is Receiving Interference From One Radar.	4-54
4-11	ARTS-IIIA/RDAS Probability Of Target Hit When Connected To ASR-8 Radar That Is Receiving Interference From Three Radars Of The Same Type	4-55

4-12 ARTS-IIIA/RDAS Probability Of Target Detection For Typical Detection Parameters And Various Combinations Of Interfering And Victim Radars 4-59

4-13 ARTS-IIIA/RDAS Probability Of False Alarm When Connected To ASR-7 Radar (MTI Channel) That Is Receiving Interference From Three Radars Of The Same Type 4-63

4-14 ARTS-IIIA/RDAS Probability Of False Alarm When Connected To ASR-8 Radar (MTI Channel) That Is Receiving Interference From Three Radars Of The Same Type 4-64

4-15 ARTS-IIIA/RDAS Probability Of Target Detection When Connected To ASR-7 Radar (MTI Channel) That Is Receiving Interference From Three Radars 4-65

4-16 ARTS-IIIA/RDAS Probability Of Target Detection When Connected To ASR-8 Radar (MTI Channel) That Is Receiving Interference From Three Radars Of The Same Type 4-66

4-17 ARTS-IIIA/RDAS Probability Of Clutter Hit When Connected To Victim Radr That Is Receiving Interference From Three Radars Of The Same Type 4-71

4-18 ARTS-IIIA/RDAS Probability Of Clutter Parameter Decrement And Increment Due To Interference Effect On Normal Channel Clutter Hits 4-74

4-19 ARTS-IIIA/RDAS Probability Of MTI Hit Count Threshold And Sliding Window Isolated Hit Sum Change Due To Interference. 4-74

C-1 MTI Canceller Transfer Properties C-20

C-2 Signal-To-Noise Improvement (In Decibels) Relative To Detection Of $I^2 + Q^2$ (Fluctuating Signal), Single Pulse C-35

D-1 Feedback Integrator Peak Signal-To-Noise Enhancement For Normal Channel D-9

D-2 Target Azimuth Shift Caused By Feedback Integration D-19

D-3 Probability Of Noise Causing The Integrator To Be In State E_j D-40

D-4 Probability Of Noise Causing The Modified FAA Integrator To Be In State E_j D-42

D-5 Probability Of Noise Causing The Integrator To Be In State E (Simulated) D-43

D-6 Probability Of Desired Signal Target Return Pulse Train Of 20 Pulses Causing The FAA Modified Integrator To Be In State E D-48

G-1 ASR-5 System Characteristics G-2

G-2 ASR-7 System Characteristics G-3

G-3 ASR-8 System Characteristics G-4

G-4 WSR-57 System Characteristics G-5

G-5 WSR-74S System Characteristics G-6

G-6 AN/FPS-6 System Parameters G-7

G-7 AN/GPN-20 System Characteristics G-8

G-8 AN/CPN-4 System Characteristics G-9

G-9 AN/MPN-13 System Characteristics G-10

G-10 AN-TPN-24 System Characteristics G-11